

	SenseAnywhere AccessPoint Model 20-01-10 The SenseAnywhere AccessPoint is an economic and reliable plug and play device that connects wireless sensors like the AssetSensor and AiroSensor to the Cloud service of SenseAnywhere.
Wireless:	
Frequency	ISM Band, 868 MHz (Region 1) or 915MHz (Region 2)
Wireless Protocol	SenseAnywhere wireless protocol with automatic service discovery and seamless roaming
Wired Protocol	10Mbit Ethernet 10BASE-T, TCP/IP port 80, DHCP, DNS
Connections:	
Power connector	DC plug, 5mm / 2.1mm
Ethernet connector	Shielded RJ45
Option to provide power to the AccessPoint by using an optional Power splitter / combiner cable set available as accessory.	
Power requirements:	
Voltage	5V DC
Current	175mA
Supplied power adapter has an exchangeable power plug and is standard supplies with a 2-pole Euro plug. It has a 1m DC cable	
Mounting:	
Preferred mounting position is vertical , hinged on a screw using the key-hole in the back. Alternatively the AccessPoint can be hung at its cables. Try to avoid mounting on metal surfaces, reinforced concrete walls, inside metal racks or cabinets.	
Dimensions AccessPoint:	
Height	90mm
Width	55mm
Depth	27mm
Indicator (3-colour LED) status:	
Red	Powered
Orange	DHCP resolution successful. Can communicate in the local network
Green	Connection with the SenseAnywhere Cloud; system is operational
Green blinking	Communication with Cloud is taking place
Weight:	
AccessPoint	58 g
Power Supply	68 g
Complete Package	215 g