

Data Sheet

Function/Arbitrary Waveform Generator

FI 5500GA Series

- ◆ DDS technology, dual-channel output
- ◆ 125MSa/s sample rate, 14bit vertical resolution.
- ◆ 5 types of standard output waveform, built-in 48 arbitrary waveforms
- ◆ Complete set of modulation functions: AM, FM, PM, FSK, ASK, PWM, linear/logarithmic sweep, burst
- ◆ Abundant input/output: waveform output,
- ◆ Synchronous signal output, External modulation source input, 10MHz clock input, external trigger input, internal trigger output etc
- ◆ Channel coupling and duplication function
- ◆ Built-in accurate frequency counter enables to measure ranges 100MHz-200MHz (single channel)
- ◆ Standard interfaces: USB Device, USB Host, Optional interface: GPIB
- ◆ High precision clock(1ppm & 10ppm)is optional
- ◆ Supplied with powerful arbitrary editing software
- ◆ Remote control support

Reasonable price & outstanding performance

FI 5500GA series Function/Arbitrary Waveform Generator is a new family member of SIGLENT with friendly design: 3.5 inch TFT-LCD display; Built-in Chinese/English language; Online help function; Support USB and internal storage, facilitate files management; Special connection terminal for grounding



Application fields:

- ◆ Analog sensor
- ◆ Simulation environment signals
- ◆ Circuit function test
- ◆ IC test
- ◆ Researching and training

Edit arbitrary waveform

Enables edition of 14-bit 16kpts arbitrary output waveforms, Arbitrary editing software EasyWave provides 9 standard waveforms: Sine, Square, Ramp, Pulse, ExRise, ExpFall, Sinc, Noise and DC, which meets all engineers' basic needs; In addition, it provides plenty of ways of manual drawing, point-to-point line drawing and arbitrary point drawing. It facilitates to create complex waveforms; Multi-file screen management helps users to edit multiple-waveform simultaneously. It provides 10 Storage in non-volatile RAM. You can edit and store more waveforms by EasyWave.

Arbitrary waveform output

Built-in 48 arbitrary waveforms, including math, engineering and other commonly-used waveforms

Complete set of modulation functions, sweep output, burst output

- ◆ Complete set of modulation functions: AM, DSB-AM, FM, PM, FSK, ASK, PWM, the modulation waveform can be observed directly, which it is suitable for education and training;
- ◆ Sweep output: change output frequency from starting frequency to ending one within sweeping time, Sweeping time range: 1ms~500s. The carrier can be Sine, Square, Triangle and Arbitrary waveforms.
- ◆ Burst output: It can periodically generate pulse sequence. Internal counter and external control signal are available to control burst output.

Dual-channel Coupling,

Duplicating function

- ◆ Channel coupling: after setting base channel and coupling frequency/phase difference, the frequency/phase of the other channel will change according to base channel, keeping set coupling frequency/phase difference fixed.
- ◆ Channel duplicating: allows to duplicate parameters from one channel to the other.

Built-in frequency counter

Wide frequency range: 100mHz~200MHz.
Measurable parameters: frequency, period, duty-cycle, positive pulse width, negative pulse width

Setting: it can set DC/AC coupling, trigger level and high frequency rejection.

FI 5500GA Series DataSheet

Specification

Model	FI 5505GA	FI 5510GA	FI 5520GA	FI 5525GA	FI 5550GA
Max. output frequency	5MHz	10MHz	20MHz	25MHz	50MHz
Output channels	2				
Sample rate	125MSa/s				
Arbitrary waveform length	16kpts				
Frequency resolution	1μHz				
vertical resolution	14bits				
Waveform	Sine, Square, Ramp, Pulse, Gaussian Noise. 48built-in arbitrary waveforms(include DC)				
Modulation	AM, DSB-AM, FM, PM, FSK, ASK, PWM, Sweep, Burst				
Frequency counter	Frequency range:100mHz~200MHz				
Standard interface	USB Host & Device				
Optional interfaces	GPIB(IEEE-488)				
Dimension	W x H x D=229mm x 105mm x 281mm				

Attention:

All these specifications apply to the FI 5500GA Series Function/Arbitrary Waveform Generator unless otherwise explanation. To satisfy these specifications, the following conditions must be met first:

1. The instrument has been operating continuously for more than 30 minutes within specified operating temperature range (18°C~28°C).
2. The temperature variation does not exceed 5°C.

Note: all specifications are guaranteed unless where noted 'typical'.

Frequency Specification					
	FI 5505GA	FI 5510GA	FI 5520GA	FI 5525GA	FI 5550GA
Waveform	Sine, Square, Ramp, Pulse, Noise, Arbitrary				
Sine	1μHz ~ 5MHz	1μHz ~ 10MHz	1μHz ~ 20MHz	1μHz ~ 25MHz	1μHz ~ 50MHz
Square	1μHz ~ 5MHz	1μHz ~ 10MHz	1μHz ~ 20MHz	1μHz ~ 25MHz	1μHz ~ 25MHz
Pulse	500μHz ~ 5MHz	500μHz ~ 5MHz	500μHz ~ 5MHz	500μHz ~ 5MHz	500μHz ~ 5MHz
Ramp/Triangular	1μHz ~ 300kHz	1μHz ~ 300kHz	1μHz ~ 300kHz	1μHz ~ 300kHz	1μHz ~ 300kHz
Gaussian white noise	>5MHz (-3dB)	>10MHz (-3dB)	>20MHz (-3dB)	>25MHz (-3dB)	50MHz (-3dB)
Arbitrary	1μHz ~ 5MHz	1μHz ~ 5MHz	1μHz ~ 5MHz	1μHz ~ 5MHz	1μHz ~ 5MHz
Resolution	1μHz				
Accuracy	Within 90days±50ppm within 1 year ±100ppm 18°C~28°C				
Temperature coefficient	<5ppm/°C				

Sine Spectrum Purity	
Harmonic Distortion	CH1/CH2
DC~1MHz	-60dBc
1MHz~5MHz	-53dBc
5MHz~25MHz	-35dBc
25MHz~50MHz	-32dBc
Total harmonic waveform distortion	DC~20kHz, 1Vpp<0.2%
Spurious signal(non-harmonic)	DC~1MHz<-70dBc 1MHz~10MHz<-70dBc+6dB/spectrum phase
Phase noise	10kHz Offset, -108dBc/Hz(typical value)

Square		
Rise/fall time		<12ns(10% ~ 90%)
Overshoot		<5%(typical, 1kHz, 1Vpp)
Duty Cycle	1μHz ~ 10MHz	20%~80%
	10MHz(exclude)~20MHz	40%~60%
	20MHz(exclude)~25MHz	50%
Asymmetric(50% Duty Cycle)		1% of period+20ns(typical, 1kHz, 1Vpp)
Jitter		0.1% of period(typical, 1kHz, 1Vpp)

FI 5500GA Series DataSheet

Ramp/Triangle	
Linearity	<0.1% of Peak value output(typical,1kHz,1Vpp,100% symmetric)
Symmetry	0%~100%

Pulse	
Pulse width	1800s, Max. 16 ns, Min. 8 ns resolution
Rise/Fall time (10% ~ 90%,typical,1 kHz,1Vpp)	7ns
Duty Cycle	0.1%Resolution
Overshoot	<5%
Jitter(pk-pk)	8ns

Arbitrary	
Waveform length	16k points
Vertical resolution	14bits
Sample rate	125MSa/s
Min. Rise/Fall time	7ns(typical)
Jitter(pk-pk)	8ns(typical)
Storage in non-volatile RAM memory (10 in total)	10waveforms

Output Specification		
Output	CH1	CH2
Amplitude	2mVpp~10Vpp(50 Ω , $\leq$ 10MHz) 2mVpp~5Vpp(50 Ω ,>10MHz) 4mVpp~20Vpp(high impedance, $\leq$ 10MHz) 4mVpp~10Vpp(high impedance,>10MHz)	2mVpp~3Vpp(50 Ω) 4mVpp~6Vpp(high impedance)
Vertical accuracy (100 kHz sine)	$\pm(0.3\text{dB}+1\text{mVpp of setting value})$	$\pm(0.3\text{dB}+1\text{mVpp of setting value})$
Amplitude flatness (compared to 100 kHz sine,5Vpp)	$\pm 0.3 \text{ dB}$	
Channel phase deviation	<400ps (classic value,sine,50MHz,4vpp)	
Cross talk	<-70dBc	

DC Offset		
Range(DC)	$\pm 5\text{V}(50 \Omega)$ $\pm 10\text{V}(\text{high impedance})$	$\pm 1.5\text{V}(50 \Omega)$ $\pm 3\text{V}(\text{high impedance})$

Offset accuracy	$\pm(\text{setting offset value} *1\%+3\text{mV})$	$\pm(\text{setting offset value} *1\%+3\text{mV})$
-----------------	---	---

Waveform Output		
Impedance	50 Ω (typical)	50 Ω (typical)
Protection	short-circuit protection	short-circuit protection

AM Modulation(CH1/CH2)	
Carrier	Sine, Square, Ramp, Arbitrary(except DC)
Source	Internal/External
Modulation waveform	Sine, Square, Ramp, Noise, Arbitrary (2mHz ~ 20kHz)
Modulation depth	0% ~ 120%
FM Modulation(CH1/CH2)	
Carrier	Sine, Square, Ramp, Arbitrary(except DC)
Source	Internal/External
Modulation waveform	Sine, Square, Ramp, Noise, Arbitrary(2mHz~20kHz)
Frequency deviation	0 ~0.5*bandwidth 10 μ Hz resolution
PM Modulation(CH1/CH2)	
Carrier	Sine, Square, Ramp, Arbitrary(except DC)
Source	Internal/External
Modulation waveform	Sine, Square, Ramp, Noise, Arbitrary(2mHz~20kHz)
Phase Deviation	0~360°, 0.1°Resolution
FSK Modulation(CH1/CH2)	
Carrier	Sine, Square, Ramp, Arbitrary(except DC)
Source	Internal/External
Modulation waveform	50% duty-cycle square waveform(2mHz~50kHz)
ASK Modulation(CH1/CH2)	
Carrier	Sine, Square, Ramp, Arbitrary(except DC)
Source	Internal/External
Modulation waveform	50%duty-cycle square waveform(2mHz~50kHz)
PWM Modulation(CH1/CH2)	
Frequency	500 μ Hz~20kHz
Source	Internal/External
Modulation waveform	Sine, Square, Ramp, Arbitrary(except DC)
External Modulation range	-6V~+6V (maximum width deviation)
Sweep(CH1/CH2)	
Carrier	Sine, Square, Ramp, Arbitrary(except DC)
Type	linear/logarithmic
Direct	Up/down
Sweep time	1ms~500s
Trigger source	Manual, external, internal

FI 5500GA Series DataSheet

Burst(CH1/CH2)	
Waveform	Sine, Square, Ramp, Pulse, Arbitrary(except DC)
Type	Count(1~50,000 periods),infinite, Gated
Start/Stop phrase	0°~+360°
Internal period	1μs~500s
Gated source	External trigger
Trigger source	Manual, External or Internal

Rear Panel Connector	
External modulation	±6V=100% modulation>5k Ω input impedance
External trigger	TTL compatible
Note: The external input voltage can't be over ±6V, otherwise instrument gets damaged.	

Trigger Input	
Input Level	TTL compatible
Slope	Up or down (optional)
Pulse width	>100ns
Input impedance	>5k Ω ,DC coupling

Trigger Output	
Voltage level	TTL compatible
Pulse width	>400ns
Output impedance	50 Ω (typical)
Max. frequency	1MHz

SYNC Output	
Voltage level	TTL compatible
Pulse width	>50ns
Output impedance	50 Ω (typical)
Max. frequency	2MHz

Frequency Counter	
Measurement	Frequency, Period, Positive/negative pulse width, duty cycle
Frequency range	Single Channel:100mHz~200MHz
Frequency resolution	6bits/s
Voltage range (non-modulated signal)	

Manual	DC coupling	DC offset range	±1.5VDC
		100mHz~100MHz	50mVrms~±2.5V
		100MHz~200MHz	100mVrms~±2.5V
	AC coupling	1Hz~100MHz	50mVrms~5Vpp
		100MHz~200MHz	100mVrms~5Vpp
Pulse width and duty-cycle measurement	1Hz~10MHz(50mVrms~5Vpp)		
Input adjustment	Input impedance		1MΩ
	Coupling mode		AC,DC
	High-frequency rejection		ON/OFF
Trigger level range	-3V~ +1.8V		

General Specification

Display	
Display type	3.5inch'TFT-LCD
Resolution	320×RGB×240
Color depth	24bit
Contrast Ratio	350:1(typical)
Luminance	300cd/m ² (typical)
Power	
Voltage	100~240 VAC _{RMS} , 45~66Hz, CATII
	100~127 VAC _{RMS} , 45~440Hz, CATII
Consumption	<30W
Fuse	1.25A,250V
Environment	
Temperature	Operation:0°C~40°C
	Storage:-20°C~60°C
Humidity range	Below +35°C:≤90% relative humidity
	+35°C~+40°C:≤60% relative humidity
Altitude	Operation: below 3,000 meters
	Storage: below 15,000 meters
Others	
Dimension	Width:229mm
	Height:105mm
	Depth:281mm
Weight	N.W: 2.6Kg
	G.W: 3.4Kg
IP protection	
IP2X	
Calibration Cycle	

FI 5500GA Series DataSheet

1year

Purchase Information

Product Name

FI 5500GA Function/Arbitrary Waveform Generator

Models:

FI 5550GA 50MHz

FI 5525GA 25MHz

FI 5520GA 20MHz

FI 5510GA 10MHz

FI 5505GA 5MHZ

Standard Accessories

- A User Manual
- A Certification
- A Guaranty Card
- An CD(including EasyWave2.0 computer software system)
- A Power Cord that fits the standard of destination country
- A USB Cable

Optional Accessories

- BNC cable
- GPIB-USB Adapter