Castle 'SONUS' GA116B and GA216B Pocket Sound Meters

The Castle SONUS range of pocket sized sound level meters bring simplicity and power to the worlds of Noise at Work and Environmental sound monitoring. From a basic sound pressure meter to full data-logging, combined sound and dosemeter, the range of systems covers a wide diversity of applications.

The entry level of the Castle Pocket Range of Sound Level Meters is the SONUS B(GA116B & GA216B), a feature packed, pocket instrument that is fully compliant with IEC 61672-1:2002. This meter gives simultaneous sound pressure (Lp) and peak (Cpeak) measurement for a multitude of tasks including Fire Alarm Testing and initial spot-check assessments to the Noise at Work Regulations 1989. It has a high-specification measurement microphone and is cased in tough, crack resistant ABS plastic.

> Mobility of instrumentation is essential for effective noise measurement. As the name indicates, the Castle SONUS 'Pocket Meters' pack all the necessary features into pocket sized proportions

The data-logging versions have a USB connection and are compatible with the Castle dBdataPRO software, where data can be presented in the desired format and copied and pasted into other applications, so you don't have to change the way you have always completed your reports.

There are a number of system packages available to suit many applications from simple tasks such as alarm monitoring, to a fully weatherproof system for long-term environmental monitoring, there are also dedicated packages for Noise at Work requirements.

POCKET POWER

Feature-Packed

Designed for **Engineers**, **Industrial Safety Officers** and anyone with a need for competent sound measurements. This meter can assist with compliance to the Health and Safety at Work Act; Noise at Work regulation 1989. The Castle GA116B is a great general purpose sound level meter that will fit in your pocket and be ready whenever you need it.

- Sound Pressure (Lp) to 0.1 dB resolution
- 'A' and 'C' frequency weighting (toggle)
- 'Slow' and 'Fast' Time weighting (toggle)
- Simultaneous measurement of Lp, Lmax, and Cpeak
- Lmax maximum Lp hold (rms.)
- Cpeak maximum peak level
- Elapsed time (running time hrs, min, sec)
- Overload and Under-range indication
- Battery condition (Life approx. 12 hours)

A Tough Case for all Weathers...

The physical design and construction of the Castle GA116B casing is extremely tough and durable, made from a substantial thickness of ABS, crack resistant plastic, the GA116B will stand up to almost any industrial environment.

Simplicity and Power...

Using the meter could not be simpler. The simple operating system uses logical keys to immediately display the information you need. The power of this little wonder means that it can measure simultaneous 'A' weighted levels as well as monitoring the Peak levels. This is a vital feature for many assessment tasks.

Future-Proof...

The built in software for this meter is designed to suit future upgrading for feature enhancements, legislative changes or instrument upgrades. Details are mailed to customers as soon as they become available. With the Castle Pocket meters, you will always be in step with the law and market requirements





technical safety & environmental solutions

SONUS B (GA116B & GA216B) SPECIFICATION

Range of Pocket sized Sound Level Meters and combined Personal Sound Exposure Meters

DESCRIPTION

GA116B Type 1, Sound Level Meter GA216B Type 2, Sound Level Meter

APPLICABLE STANDARDS

IEC 61672-1:2002 (Integrating, Sound Exposure and Sound Level Meters)

MICROPHONE AND PREAMPLIFIER

Type 2 Pre-Polarised $\frac{1}{2}$ " (13.2 mm) Electret Free-Field, Electret Condenser Microphone: 20Hz - 8KHz \pm 2dB -32 dB \pm 3 dB re 1V/Pa Custom pre-amplifier design Typical actuator to free-field correction factor (based on

500Hz=0) is shown below

| 20Hz: 0 | 1kHz: 0 |
|-----------|---------------|
| 25Hz: 0 | 1.25kHz: +0.1 |
| 31.5Hz: 0 | 1.6kHz: +0.3 |
| 40Hz: 0 | 2kHz: +0.4 |
| 50Hz: 0 | 2.5kHz: +0.5 |
| 63Hz: 0 | 3.15kHz: +0.8 |
| 80Hz: 0 | 4kHz: +1.2 |
| 500Hz: 0 | 5kHz: +1.6 |
| 630Hz: 0 | 6.3kHz: +2.3 |
| 800Hz: 0 | 8kHz: +3.6 |

DISPLAY

Back-lit LCD panel (8x1 Characters) Alpha-Numeric display for measured results

LEVEL RANGE

Measuring Range: 35-140 Linear operating range (IEC61672-1): 65dB 3 Measurement Ranges (IEC61672-1): 35-100 55-120 - Reference Range 75-140

NOISE FLOOR

Typical 'A' Weighting <32 dB(A) rms. 'C' Weighting <38 dB(C) rms.

FREQUENCY WEIGHTING

'A' and 'C' to IEC 61672-1:2002 and IEC 60651:1979+A1+A2

FREQUENCY RANGE

20 Hz - 8 kHz (including microphone) 1 Hz - 20 kHz (electrical characteristics)

TIME WEIGHTING

Slow and Fast

INSTRUMENT RESPONSE

Simultaneous rms. and Peak

MEASUREMENT PARAMETERS

Lp (Sound Pressure Level), Lmax (maximum Level), Cpeak (Max. Peak Level) Other Displays: Elapsed time, Overload, Battery Life

CALIBRATION

Software controlled 91.0 to 120.0 dB (1kHz) in 0.1 dB steps

PROCESSING

A to D Converter: 12-bit Controller: 8MHz, micro-controller

POWER REQUIREMENTS

Batteries: 1 x 6LR61 (size PP3), Life: >12 hours (alkaline batteries, continuous operation).

SIZE AND WEIGHT

Dimensions: 60mm (width) x 35mm (depth excluding pocket clip) x 135mm (height without microphone) or 210mm (height with microphone) Weight: 220gms (including battery)

MANUALS

 $\label{eq:main_state} Multi-language \ manuals^*: \ French, \ German, \ Spanish \ and \ Italian.$

ACCESSORIES

GA601 Single Level Calibrator: **KA010** Kit Case for GA116B, GA601 and Accessories

Note: Items marked * will be available as upgrades in the near future.

In the interest of continued developments, Castle reserve the right to change the product specifications without notice

SONUS PRODUCT RANGE

Sound Meters

| | Class 1 | Class 2 | |
|----------------------------------|---------|---------|--|
| Basic– sound pres- sure level | GA116B | GA216B | |
| Integrating—(Leq) | GA116I | GA216I | |
| Data-logging | GA116L | GA216L | |

Dosemeters

| Basic Dedicated Dosemeter | GA257B |
|------------------------------|--------|
| Data-logging Dosemeter | GA257L |

To the Safety, Health and Environment Professional...

The issues faced every day by Health, Safety and Environmental professionals are vast and varied. At Castle, we have spent a lot of time developing products and services to make your life easier!

Castle Group Ltd are one of the leading international group specialists in technical safety, health and environment solutions. Whether you are in Industry, Construction, Local Authority or anywhere there are safety or environment issues, we are a resource you really could use. We can help with Noise, Vibration, Air sampling, Gas detection, Light and temperature and just about anything else that needs measuring. The following services show you how we can help

FREE Health & Safety Training Seminars!

To get you off the ground, refresh your knowledge or just to get a taste, Castle is continually running FREE Safety, Health and Environmental seminars around the country. Covering subjects from Noise at Work, to COSHH and Audiometry, the list is ever growing, as are the locations. Check out our web site for the next seminar near you.

www.castlegroup.co.uk



Castle Instruments

Dealing with many Safety, Health and Environmental issues may well mean you need access to a plethora of **equipment** and **instrumentation** to carry out measurements and assessments necessary for the job.

At Castle we can provide you with just about any of the equipment you might need. All our equipment comes with the **guarantee** of back-up and support you only get from a company with 40 years under its belt! Here are a few of the core products we can offer, but we can also source anything you may need!

Noise and Vibration Measurement Equipment Audiometers, Otoscopes and Booths Air-Sampling Pumps, Calibrators and Consumables Gas-Detection and Personal Monitors Emissions and Air Quality Light, Temperature, Humidity and Airflow

www.castlegroup.co.uk

