

Riser Bond Model 6000

MULTI-FUNCTION TELEPHONE NETWORK ANALYZER



FEATURES/KEY BENEFITS

- **Diagnostic and fault location functions in one instrument** – Integrated testing system enables the technician to diagnose and locate faults with one easy to use, high quality instrument.
- **Diagnostic Test Package**- Identify conditions on the line that can adversely affect service using the following diagnostic tools:
 - Multi-Meter** – Measure AC volts, DC volts, foreign battery, resistance and insulation resistance.
 - Pair Quality Tests** – Measure loop current, noise metallic, power influence and longitudinal balance.
- **Fault Location Test Package** - Restore existing service quicker or reclaim unused lines for new service with accurate fault location tools:
 - Time Domain Reflectometer (TDR)** – Accurately locate opens, shorts, water in cable, bad splices and cable damage with the same full-function TDR found in Riser Bond's stand-alone instruments.
 - Resistance Fault Locator (RFL)** – Three test modes. Locate resistance faults on a pair or on a single conductor.
 - Stress TDR** – This exclusive feature enhances the instrument's ability to locate faults due to moisture in the cable.
 - Open/Capacitance Meter** – Measure capacitance to the end of the pair or locate fault caused by an open circuit.
- **Ease-of-Use Features** – The soft-key menu's intuitive left-to-right operation guides the technician through logical testing steps to diagnose and locate faults. Most tests are performed using the same connection to the line.
- **Auto-Test and Fault Analysis Functions** – Press the Auto-Test key to perform a series of basic diagnostic tests. The Fault Analysis function will then suggest the appropriate fault location tool to use to most effectively locate the problem.
- **SUPER-STORE Waveform Data Storage** – Analyze TDR waveforms in a more convenient time or place. The instrument also stores Auto-Test records.
- **WAVE-VIEW Software** – View, manipulate, print and archive TDR waveforms on your computer. Document plant, certify new builds, and store waveforms for later comparisons.
- **Optional Oscillator and Probe** – One unassisted technician working at a distance from the exchange can disconnect a customer's service, identify the cable pair, open and close the circuit, and reconnect the customer after desired tests are complete.
- **Large LCD Display** – Test results and interpretive information are presented in an easy to read format on a screen that is larger than those found on many competitive units.

PRODUCT SPECIFICATIONS

PHYSICAL DIMENSIONS	
Main instrument without carrying case & accessories	
Width:	10.71 inches (272mm)
Height:	6.93 inches (176mm)
Depth:	3.15 inches (80mm)
Weight:	4.8 pounds (2.2kg)
Main instrument with carrying case & accessories	
Width:	11.18 inches (284mm)
Height:	7.80 inches (198mm)
Depth:	7.0 inches (178mm)
Weight:	7.9 pounds (3.6kg)
POWER	
Internal:	Rechargeable, 7.2V Nickel metal hydride battery pack
External:	12VAC or VDC, 1250mA power supply
Operating Time:	Greater than 5 hours, continuous without backlight
ENVIRONMENT	
Operating temperature:	0°C (+32°F) to +50°C (+122°F)
Storage temperature:	-20°C (-4°F) to +60°C (+140°F)
Humidity:	95% maximum relative humidity, non-condensing
	IEC 68-2-3
Vibration:	IEC 68-2-6
Shock (Bump):	IEC 68-2-29, 40g, 6ms,1000 shocks in each axis
Drop:	IEC 68-2-27, 1m free fall, packaged in carry case
Moisture rating:	IP54
DISPLAY	
320 x 240 dot-matrix, liquid crystal display (LCD) with CCFL backlighting	
MULTI-METER	
DC Voltage:	0 to 400V
Resolution:	0.1V
Accuracy:	1% ±0.1V
AC Voltage:	0 to 400V
Resolution:	0.1V
Accuracy:	2% ±0.1V
Foreign Battery:	2 to 400V
Resolution:	0.1V
Accuracy:	1% ±0.1V
Resistance:	0 to 1999.9Ω
Resolution:	0.1Ω
Accuracy:	0.2% ±0.2Ω
	2kΩ to 10kΩ
Resolution:	1Ω
Accuracy:	0.2% ±1Ω

INSULATION RESISTANCE	
Voltages:	50V/100V/250V/500V
0Ω to 9.99MΩ	
Resolution:	0.01MΩ
Accuracy:	2% ±0.01MΩ
10MΩ to 99.9MΩ	
Resolution:	0.1MΩ
Accuracy:	4%
100MΩ to 999MΩ	
Resolution:	1MΩ
Accuracy:	10%
OPEN/CAPACITANCE METER	
0 to 1000ft (0 to 305m)	
Resolution:	1ft (0.3m)
Accuracy:	2% ±3ft (1m)
1000ft to 10,000ft (305m to 3,050m)	
Resolution:	10ft (3m)
Accuracy:	±3%
10,000ft to 100,000ft (3,050m to 30,500m)	
Resolution:	100ft (30m)
Accuracy:	±5%
100,000ft to 150,000ft (30,500m to 45,700m)	
Resolution:	1000ft (300m)
Accuracy:	±8%
0 to 9.99nF	
Resolution:	0.01nF
Accuracy:	2% ± 0.06nF
10.0 to 99.9nF	
Resolution:	0.1nF
Accuracy:	±3%
100 to 999nF	
Resolution:	1nF
Accuracy:	±5%
1000 to 2000nF	
Resolution:	1nF
Accuracy:	±8%
PAIR QUALITY	
Loop Current:	0 to 120mA
Resolution:	0.1mA
Accuracy:	5% ±0.2mA
Noise Metallic:	0 to 50dBmC
Resolution:	1dB
Accuracy:	±2dB
Power Influence:	40 to 100dBmC
Resolution:	1dB
Accuracy:	±2dB
Longitudinal Balance:	40 to 62dB
Resolution:	1dB
Accuracy:	±2dB

TIME DOMAIN REFLECTOMETER (TDR)

Loaded and non-loaded cable

Maximum Ranges:

Live waveform:

63,700 feet (19,400 meters) at 99.0% VOP

38,600 feet (11,700 meters) at 60.0% VOP

Range varies with VOP. Maximum testable cable length varies with pulse width and cable type.

Stored waveform:

11,900ft (3,600.0m) at 99.0% VOP

7,200ft (2,200.0m) at 60.0% VOP

Range varies with VOP.

Horizontal Resolution:

Up to 2,000ft (610m): <0.25ft (0.07m) at 99.0% VOP

<0.07ft (0.02m) at 30.0% VOP

Over 2,000ft (610m) 1ft. (0.3m) at any VOP

Vertical Resolution: 14 bits with 137 dots displayed

Vertical Sensitivity: Greater than 65dB

Output Signal: Pulse widths of 2ns, 25ns, 100ns, 500ns, 1.5µs, 4.4µs and 330µs

Output Balance: Variable, from 80Ω to 120Ω

Velocity of Propagation:

Two user-selectable display formats:

VOP (%): Non-loaded cable: 30.0% to 99.0%

Loaded cable: 0.8% to 20.0%

V/2: Non-loaded cable: 147.5 to 486.9ft/µs
(45.0 to 148.4m/µs)

Loaded cable: 3.9 to 98.4ft/µs
(1.2 to 30.0m/µs)

Input Protection: 400 VAC or VDC up to 60Hz

Distance Accuracy:

Accuracy will vary with cable VOP and cable type: ±0.5ft (0.15m) plus ±0.1% of reading

SOFTWARE NOISE FILTERS

Automatic/Manual Noise Filter: Multi-function/Multi-level filtering

RESISTANCE FAULT LOCATOR (RFL)

Location Range: 0 to 150kft (0 to 45km)

Resistance fault range: 0 to 50MΩ

Accuracy:

3-Wire Test: ±0.25% of DTS plus ±0.4Ω

4-Wire Test: ±0.25% of DTS plus ±0.25Ω

Kupfmuller Test: ±1.0% of DTS plus ±1Ω

Waveform Storage

All with full vertical resolution: 32 waveforms

RISER BOND OSCILLATOR AND PROBE

Communications for: short pair, open pair, exchange connect, disconnect, pair identification tone.

ACCESSORIES:

Standard: Operator's Manual, 12VDC charger, nylon carry/ accessory bag, shoulder strap, 2 sets telco connection leads plus ground lead, pair shorting strap, VOP card.

Technological advances allow changes in specifications and/or components
Changes may be made without notification.



© 2013 Radiodetection Ltd. All rights reserved. Radiodetection is a subsidiary of SPX Corporation. SPX, the green ">" and "X" are trademarks of SPX Corporation, Inc. Radiodetection and Riser Bond are trademarks of Radiodetection Ltd. Due to a policy of continued development, we reserve the right to alter or amend any published specification without notice. This document may not be copied, reproduced, transmitted, modified or used, in whole or in part, without the prior written consent of Radiodetection Ltd.

90/RB-MODEL-6000/ENG/01

DISTRAME S.A. - Parc du Grand Troyes - Quartier Europe Centrale - 40, rue de Vienne - 10300 SAINTE-SAVINE
Tél. : +33 (0)3 25 71 25 83 - Fax : +33 (0)3 25 71 28 98 - E-mail : infos@distrame.fr - Site internet : www.distrame.fr