



The OPUS20E offers the highest flexibility and is excellent value for money. It allows the connection of up to 4 external temperature and relative humidity sensors, as well as 2 further analogue sensors. Intelligent BUS sensors can be integrated...

- **Parameters measured**

Measurement of Input voltage 0-1V, Current measurement - 2-wires, Current measurement - 3-wires, Thermocouple K, Thermocouple J, Thermocouple S, PT100

- **Measurement technology**

Input voltage 0-1V, Current measurement - 2-wires, Current measurement - 3-wires, Thermocouple K, Thermocouple J, Thermocouple S, PT100

- **Product highlights**

LAN datalogger with built-in sensors and the highest precision and with up to 10 external channels/sensors per Opus20E.

- **Interfaces**

USB (Cable and Monitoring Software SmartGraph3 included)

- **Article number**

8120.30, 8120.30N, 8120.31, 8120.31N

Air flow and differential pressure sensors are typically connected to the OPUS20E via analogue inputs as opposed to the maximum of 4 external temperature or humidity sensors that can be integrated via a digital BUS protocol. In connection with its LAN capabilities, the Opus20E is able to realize universal measurement networks in real time. For standard applications the Smart-Graph 3 comes into play, and in order to fulfil the 21 CFR 11

guidelines the well-established and proven MCPS7 software is available.

General	
Dimensions	180 x 78 x 32 mm
Measuring interval	10/30 s, 1/10/12/15/30 min, 1/3/6/12/24 h
Construction	Plastic housing
Operating time with battery	> 1 Year
Data storage	16 MB, 3,200,000 measured values
LC-Display	Height 90 x 64 mm
Weight	Approx. 250 g
Included in delivery	PC - Windows Software SmartGraph 3 for graphical and numerical representation of measured values / Instructions/ data cable/ battery/ WAGO connector / DIN rail bracket
Interface	USB, LAN
Storage interval	1/10/12/15/30 min, 1/3/6/12/24 h
Power supply	4 x LR6 AA Mignon, USB
Operating temperature	-20...50 °C
Bus interface	RS485

Input voltage 0-1V	
Measuring range	0 ... 1 V
Unit	V
Accuracy	+/- 200 μ V +/- 0.1 % of measured value
Resolution	500 μ V

Current measurement - 2-wires	
Measuring range	4 ... 20 mA
Unit	mA
Accuracy	$\pm$ 4 μ A $\pm$ 0.1 % of measured value
Resolution	5 μ A

Current measurement - 3-wires	
Measuring range	0 ... 20 mA
Unit	mA
Accuracy	$\pm$ 4 μ A $\pm$ 0.1 % of measured value
Resolution	5 μ A

Thermocouple K	
Measuring range	-200 ... 1200 °C
Unit	°C
Accuracy	$\pm$ 1 °C +/- 0.5 % of measured value at -200 °C ... 0 °C $\pm$ 1 °C +/- 0.2 % of measured value at 0...1200 °C
Resolution	0.2 °C

Thermocouple J

Measuring range	-200 ... 1200 °C
Unit	°C
Accuracy	$\pm 1\text{ °C} \pm 0.5\%$ of measured value at -200 °C ... 0 °C $\pm 1\text{ °C} \pm 0.2\%$ of measured value at 0...1200 °C
Resolution	0.2 °C

Thermocouple S	
Measuring range	-50 ... 1700 °C
Unit	°C
Accuracy	$\pm 1\text{ °C} \pm 0.5\%$ of measured value at -50 °C ... 0 °C $\pm 1\text{ °C} \pm 0.2\%$ of measured value at 0 °C ... 1,700 °C
Resolution	0.2 °C

PT100	
Measuring range	-200 ... 500 °C
Unit	°C
Accuracy	$\pm 0.2\text{ °C} \pm 0.1\%$ of measured value
Resolution	0.02 °C

DISTRAME S.A. - Parc du Grand Troyes - Quartier Europe Centrale - 40, rue de Vienne - 10300 SAINTE-SAVINE
Tél. : +33 (0)3 25 71 25 83 - Fax : +33 (0)3 25 71 28 98 - E-mail : infos@distrame.fr - Site internet : www.distrame.fr