

Passive 1X/10X Voltage Probe

▶ P2220



▶ P2220.

P2220 Passive Voltage Probe

The P2220 200-MHz Passive Voltage Probe permits selection of 1X or 10X attenuation, using a switch located on the probe head.

This probe is compatible with TDS200, TDS1000, TDS2000, and TPS2000 Series oscilloscopes. The P2220 probe also provides floating measurement capability up to 30 V_{RMS} with TPS2000 Series oscilloscopes only. **(Note:** Do not float with TDS2000, TDS1000 or TDS200 Series oscilloscopes.)

▶ Features & Benefits

- 1X/10X Attenuation
- 200 MHz Bandwidth
- 1.5 Meter Length
- UL3111-1, CSA1010.1, EN61010-1, EN61010-2-031 and IEC61010-2-031

▶ Applications

- Relative Low Frequency Measurements
- Low Frequency Computer and Telecom Measurements
- Power Supplies
- Low Frequency Amplifiers

COMPUTING

COMMUNICATIONS

VIDEO

P2220 Passive Voltage Probe

▶ P2220

▶ Characteristics

X10 Position

Bandwidth – DC: 200 MHz.

Probe Length – 1.5 m.

Attenuation Ratio – 10:1.

Compensation Range – 15 to 25 pF.

Input Capacitance – 17.0 pF.

Input Resistance – 10 M Ω .

Maximum Input Voltage – 300 V CAT II.

Maximum Voltage Between Reference Lead and Earth Ground – 30 V_{RMS}^{*1}.

X1 Position

Bandwidth – DC: 6 MHz.

Probe Length – 1.5 m.

Attenuation Ratio – 1:1.

Compensation Range – All scopes with 1 M Ω input.

Input Capacitance – 110 pF.

Input Resistance – 1 M Ω .

Maximum Input Voltage – 150 V CAT II.

Maximum Voltage Between Reference Lead and Earth Ground – 30 V_{RMS}^{*1}.

^{*1} The float voltage must be subtracted from the tip to earth ground voltage. For example, if the reference lead is floated to 30 V_{RMS}, the tip voltage to the reference lead is limited to 270 V_{RMS}.

▶ Ordering Information

P2220

1X/10X, 200 MHz Passive Voltage Probe.

Includes: Retractable hook tip (013-0318-00), 6 in. ground lead (196-3466-02), Adjustment tool (003-1873-00), Marker band set (016-1315-00), Instruction manual (071-1464-00).



Tektronix
Enabling Innovation

DISTRAME S.A. - Parc du Grand Troyes - Quartier Europe Centrale - 40, rue de Vienne - 10300 SAINTESAVINE
Tél. : +33 (0)3 25 71 25 83 - Fax : +33 (0)3 25 71 28 98 - E-mail : infos@distrame.fr - Site internet : www.distrame.fr