

Genuine glass
surface with high
resolution colour
display

X(per) P(rofessional) Series

XP200/XP201

- TFT LCD, anti-glare colour display
- Capacitive touch screen
- Sampling rate 1s
- Data recording simultaneously on up to 3 channels
- Graphical analysis including standard deviation
- Integrated flash memory with space for up to 200 data blocks, or up to three hours continuous recording
- USB port for data transfer to Smartgraph 3 (included in delivery)
- Multilingual interface
- Numerous dimensions calculated
- Online firmware update



Hand-held measuring device XP200/ XP201 for measuring temperature and humidity



X-pert range for humidity and temperature measurements in climate and environmental technology.

Hand-held measuring device XP200			Order No.
Temperature and humidity measuring device compatible with various intelligent sensors.			5820.00
Technical data	Dimensions	170 x 62 x 34 mm	
	Weight	Approx. 205g	
Storage conditions	Permitted ambient temperature	-20...60°C	
	Permitted rel. humidity	<90% RH non-condensing	
Operating conditions	Permitted rel. humidity	<90% RH (20g/m³) non-condensing	
	Permitted altitude above sea level	4000m	
	Power supply	4 Alkaline LR6 AA 1.5V / USB 5V	
Power supply	Active power consumption	Approx. 400mW	
	Battery life passive	Approx. 1 year	
	Battery life active	Min. 24 hours	
	Sensor power supply	5.5V ± 10% DC, max. 200mA	
Data storage	Integrated data storage	Up to 200 data/approx. 1 Mio measured values	
Interface	USB	Cable and SmartGraph3 software included	
Resolution	Definition of measured values	2 decimal places	
Display	Control	Touch screen, capacitive	
	Technology	TFT, resolution 240x320, 65k colours, very good contrast due to Piezoresistive technology	
	Surface, toughened glass	Degree of hardness: 7, scratch-resistant	
Integrated air pressure sensor	Measuring range (full accuracy)	800...1,100mbar	
	Accuracy at 25°C, 1013.25mbar	0.5mbar	
	Long-term stability	typ. - 1mbar/year	
	Measurement resolution	0.024mbar	
	Measuring principle	Piezoresistive	
Calculated measurement categories for external temperature/humidity sensors	Mathematical:	MIN/MAX/AVG/HOLD	
	Temperature (°C/°F)		
	Rel. humidity (% RH)		
	Rel. humidity of ice (% RH)		
	Water vapour density (absolute humidity) g/m³		
	Dew point temperature °C/°F		
	Frost point temperature °C/°F		
	Mixing ratio at saturation (100%) g/kg		
	Volume fraction of water vapour / mass fraction of water vapour (%)		
	Wet-bulb temperature °C/°F		
	Ice-bulb temperature °C/°F		
	Specific Enthalpy (mass of air) kJ/kg		
	Saturation vapour pressure above ice/water (hPa)		
	Water vapour particle pressure (hPa)		
	Air density kg/m³		
Accessories	Extension and/or connecting cable for digital sensor, 2m	8120.KAB2	
	Extension and/or connecting cable for digital sensor, 10m	8120.KAB10	



XP201 Order No. 5810.20
*High quality wooden case and
 High-precision Temperature/Humidity Sensor
 Order No.8130.TFF from page 26
 are included in delivery.*

Compatible sensors for XP200		Page
Temperature/ humidity	Digital TFF20	24
	High-precision Temperature/Humidity Sensor	26
	Allround SDI	24
	5 mm diameter SDI	25
	High temperature SDI	25
CO₂	CO ₂ Sensor	26