

Easy to set up!

Simply plug in the Z3210 wireless adapter and your compatible HIOKI device is Bluetooth® ready!



Get connected!

Work even smarter with our new Z3210 wireless adapter! Now you can create and share graphical reports in a flash!

Z3210 is a Bluetooth® wireless adapter that will:

- Increase your work efficiency, by eliminating human errors from manual reporting
- Transfer readings on instruments to easy-to-read graphical reports to prove integrity
- Increase your work productivity & save costs!
- Provide additional new functions for HIOKI devices such as waveform display & more!



Easy set up



GENNECT Cross App



HIOKI	DATE	YYYY/MM/DD	TEMPERATURE	HUMIDITY					
Insulation resistance value	Unit	Judgement	Current value	Unit	Judgement				
101	M Ohm	PASS	3.11	A	PASS				
101	M Ohm	PASS	3.12	A	PASS				
101	M Ohm	PASS	3.12	A	PASS				
101	M Ohm	PASS	4.12	A	PASS				
101	M Ohm	PASS	3.12	A	PASS				
101	M Ohm	PASS	3.12	A	PASS				
101	M Ohm	PASS	3.12	A	PASS				

Excel® Direct Input

Specifications

Operating environment	Indoors, pollution degree 2, operable at an altitude specified in specifications of each measuring instrument to which the adapter is attached	GENNECT Cross App Confirmed compatible OSs	iOS 13 or later, Android 9 or later, Bluetooth® 4.0 or later
Operating temperature and humidity (Storage temperature and humidity)	-30°C (-22°F) to 70°C (158°F) 90% RH or less (no condensation)	Excel® Direct Input Confirmed compatible OSs	Windows 10, iOS 13 or later, Android 9 or later, Bluetooth® 4.0 or later
Standards	Safety: EN61010, RF: EN300 328, RF EMC: EN301 489-1, EN301 489-17, Exposure: EN62479	Bluetooth® Communication distance	About 10 m (line-of-sight distance)
Maximum attaching/detaching count	5000 times (Can be switched between compatible measuring instruments)	Product warranty period	3 years (except for the connector. Depending on your tablet/smartphone, you may not be able to connect)
		Dimensions and Mass	Approx. 16.4mmW × 6.7mmH × 15.6mmD (0.65" W × 0.26" H × 0.61" D), Approx. 1.5 g (0.05 oz.)
		Accessory	Instruction manual

Model



Model: WIRELESS ADAPTER Z3210

Model No. (Order code): **Z3210**



Z3210 web site

For more information on supported regions and products, please visit this dedicated site.

Compatible products (scheduled included)



AC LEAKAGE CLAMP METER
CM4001, CM4002, CM4003



AC CLAMP POWER METER
CM3286-50



AC CLAMP METER
CM4141-50



AC/DC CLAMP METER
CM4371-50
CM4373-50
CM4375-50



DIGITAL MULTI METER
DT4261



BATTERY TESTER
BT3554-50



DIGITAL PHASE DETECTOR
PD3259-50



INSULATION TESTER
IR4057-50



EARTH TESTER
FT6031-50



CLAMP ON EARTH TESTER
FT6380-50

More compatible HIOKI products and apps are on their way



Downloading GENNECT Cross

GENNECT Cross is a free app. Download it to your tablet or smartphone from Google Play™ or App Store™. Simply search for "HIOKI" and download "GENNECT Cross" today!



Note: Company names and product names appearing in this catalog are trademarks or registered trademarks of various companies. *The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by HIOKI E.E. CORPORATION is under license.

HIOKI
HIOKI E. E. CORPORATION

HEADQUARTERS
81 Koizumi,
Ueda, Nagano 386-1192 Japan
<https://www.hioki.com/>



Scan for all regional contact information

DISTRIBUTED BY

DISTRAME

Parc du Grand Troyes - 40 rue de Vienne - 10300 SAINTE-SAVINE
Tél. : 03 25 71 25 83 - infos@distrame.fr - www.distrame.fr