

VIAVI

SmartClass OTS-55

Optical Talk Set

Applications

The VIAVI SmartClass OTS-55 (optical talk set) fulfills today's communication needs during fiber installations, maintenance or troubleshooting in a very cost effective way by using one single "dark" fiber.

Headset free

The SmartClass OTS-55 provides clear digital voice transmission over a single fiber. Hands-free operation makes communication even more convenient for the technician by using either a headset or the "speakerphone" mode. No matter how you use it, the SmartClass OTS-55 provides crystal clear communication any time.

Flexibility

The outstanding performance of this talk set ensures not only a communication between two SmartClass OTS-55. Indeed, its flexibility allows operation together with VIAVI T-BERD/MTS Platforms (when equipped with talk set functionalities).



Features

- ≥ 45 dB dynamic range
- Wavelength of operation: 1550 nm
- Clear digital voice transmission
- Hands-free operation
- 4-way powering
- Rugged casing



Accessories



Ock-10 Optical Connector Cleaning Kit (accessory)



Optical adapters (BN 2155) for laser source output



Worldwide compatible AC adapter/charger (SNT-121A)



Specifications

General Data	
Operating wavelength	1550 nm
Dynamic range	≥ 45 dB (single mode) Can also be used with multimode fibers (50/125/62.5/125 μm); ≥ 10 km
Optimum fiber type	Single mode 9/125 μm
Operation modes	headset or speaker phone
Compatibility	T-BERD/MTS Platforms
Display	
Graphical display	
Resolution of 128 × 64 dots	
Backlight function switchable via separated key	
Optical connector	
Interchangeable adapter system (BN 2155/00.xx)	
SC-type mounted, additional FC-type provided free of charge.	
Optional ST-type and LC-type	
2.5 mm plugs	FC, ST, SC, DIN
1.25 mm plugs	LC
Power supply	
Four dry batteries Mignon/AA, 1.5 V or NiMH rechargeable cells Mignon/AA 1.2 V	
Operating time from dry batteries (in headset mode) >60 h	
Batteries/NiCd/NiMH power saving mode	
AC line operation via separate AC adapter/charger SNT-121A	
Integrated fast battery charging function	2 hours
Electromagnetic compatibility	
Corresponds to IEC 61326 (CE conformance)	
Ambient temperature	
Nominal range of use	- 10°C to +55°C
Storage and transport	- 40°C to +70°C
Dimensions and weight	
W × H × D approximately	95 × 60 × 195 mm (3.74 × 2.36 × 7.68 in)
Weight approximately	500 g (1.1 lb)

Ordering Information

Order information	
BN 2285/01	SmartClass OTS-55, single unit
BN 2285/10	SmartClass OTS-55, pair of two units
Included with the OTS-55	
Interchangeable adapter from BN 2150/00.xx range, 4 dry batteries Mignon/AA, 1.5 V, operating manual, MT-1S belt bag	
Accessories	
BN 2155/00.32	Optical adapter ST type
BN 2155/00.06	Optical adapter SC type (SC-PC)
BN 2155/00.05	Optical adapter FC type (FC-PC, FC-APC)
BN 2155/00.07	Optical adapter LC type (LC-PC, LC-APC)
BN 2229/90.21	OCK-10 Optical Connector Cleaning Kit
BN 2277/90.01	Worldwide compatible AC adapter (SNT-121A)
BN 2237/90.02	NiMh cells, Mignon/AA size (4 required)

DISTRAME

Parc du Grand Troyes - 40 rue de Vienne - 10300 SAINTE-SAVINE
Tél. : 03 25 71 25 83 - infos@distrame.fr - www.distrame.fr



To reach the VIAMI office nearest you,
[visit viavisolutions.com/contact](http://visit.viavisolutions.com/contact)

© 2021 VIAMI Solutions Inc.
Product specifications and descriptions in this document are subject to change without notice.
Patented as described at
viavisolutions.com/patents
ots-55-ds-fop-tm-ae
30137430 900 0817